

**Marktek Inc.**  
**Your One-Stop Shop for Conductive, Resistive, & Microwave-Absorptive Materials**

**Data Sheet for SBRMC60**

ID Number:	SBRMC60
Part Number:	RTF151RS
Description:	Nylon ripstop fabric coated with silver and carbon-loaded polyurethane on one side
Thickness, mils:	4.5 (114 um)
Basis Weight, oz/yd <sup>2</sup>	1.78 (60 g/m <sup>2</sup> )
Width, in (nominal)	50 (127 cm)
Surface Resistivity, ohm/sq	<0.5
Shielding Effectiveness @ 1 GHz, db	65
Metal Adhesion*:	Pass, no metal loss
Abrasion Resistance, cycles:	1,000,000
Cold Exposure*:	No cracking
Short-term Temperature Exposure, °C:	120
Avg. Roll Length, yd.:	220 (200 m)

\*Metal adhesion, ASTM D3359; salt fog test, ASTM B117; cold exposure test samples chilled to -45°C, then flexed 180° around a 1/8" diameter rod while at -45°C.

The information provided here is for illustrative purposes only and should not be considered a product specification. As always, it is up to the user of this product to make the final determination as to whether the said product is suitable for the users intended application.

13621 Riverway Dr.  
Suite H  
Chesterfield, MO 63017

Tel: 314-878-9190  
Fax: 314-878-9558  
Email: [info@marktek-inc.com](mailto:info@marktek-inc.com)

[www.Marktek-Inc.com](http://www.Marktek-Inc.com)

